



KOLD-FLO® Ready to Use Fast-Curing Crack Filler



Prevents Cracks

from becoming potholes

KOLD-FLO® crack filler is a modified asphalt emulsion crack filler designed for maintenance of asphalt and concrete pavements. It is ideal for roads, highways, parking lots and driveways.

UNIQUE developed **KOLD-FLO** crack filler as a cost-effective repair solution that prevents cracks from becoming potholes by sealing them from the weather's destructive freeze and thaw cycles.

Ready to Use

saving you time and money

KOLD-FLO® crack filler requires no heating or special preparation, and is ready to use right out of the container. Repair crews save time being able to grab and go without waiting for the material to be ready for application.

Since no heat preparation is required, you save money by not having to waste material. The safety and portability of **KOLD-FLO** crack filler make it the crack filler of choice.

How does your crack filler compare to KOLD-FLO® crack filler?

- › **Minimal Preparation:** No waiting for kettles to heat up. Crews can be ready to go in minutes. Equipment maintenance is near zero.
- › **Easy Application:** You can apply KOLD-FLO® crack filler right from its original container with a pour pot or drum pump.
- › **Safe to Apply:** Since no heating is required, you avoid the dangerous burns that can occur from hot-applied material.
- › **Reduced Traffic Delays:** When properly applied, **KOLD-FLO** crack filler can be driven over within 30 minutes without tracking.

KOLD-FLO® crack filler is a convenient material for filling cracks without needing any special equipment or training.



KOLD-FLO® crack filler is a product of UNIQUE Paving Materials Corp.

KOLD-FLO® is a registered trademark of UNIQUE Paving Materials Corp.





1 Prepare the area

Clean out debris from the cracks so the KOLD-FLO® crack filler can completely fill the damaged area.

For best results, either sweep area with UNIQUE's STIFFWITCH® broom, a street broom or blow out debris with compressed air.

2 Apply KOLD-FLO® crack filler

Using the one-gallon bottle, a pour pot or a drum pump, pour KOLD-FLO® crack filler into the crack $\frac{3}{4}$ of the length.

Allow a few minutes for KOLD-FLO crack filler to seep completely down into the crack. KOLD-FLO crack filler fills from the bottom up.

3 Complete the repair

Push KOLD-FLO® crack filler into the crack, with a "U" shaped squeegee, allowing the excess to fill the remaining $\frac{1}{4}$ of the crack.

For cracks deeper than 2" a second application of KOLD-FLO crack filler may be needed. Wait at least one hour prior to second application.



KOLD-FLO® crack filler coverage (per gallon)

1/4" (6MM) WIDE X 1/4" (6MM) DEEP	=	300 LINEAR FEET (92 LINEAR METERS)
1/2" (13MM) WIDE X 1/2" (13MM) DEEP	=	75 LINEAR FEET (23 LINEAR METERS)
1" (25MM) WIDE X 1" (25MM) DEEP	=	25 LINEAR FEET (8 LINEAR METERS)

KOLD-FLO® crack filler is available in 440# 55-gallon drums, 38# 5-gallon pails and 8.05# 1-gallon easy pour bottles.

Call UNIQUE today to learn more about how KOLD-FLO® crack filler works in preventing cracks from becoming potholes!



KOLD-FLO® crack filler is a product of UNIQUE Paving Materials Corp.

KOLD-FLO® is a registered trademark of UNIQUE Paving Materials Corp.

