

# KOLD-FLO®

Pourable Crack Filler

KOLD-FLO® crack filler is applied in an easy three step process.



Using a broom or leaf blower, blow or sweep out debris from cracks. Cracks must be free of debris prior to application.



Pour KOLD-FLO® crack filler into three quarters of the length of the crack. Product can be applied directly from the bottle, using a pour pot or UNIQUE's CRACK-N-TACK® portable pump.



Squeegee **KOLD-FLO** crack filler into the crack using a "U" or "V" shaped squeegee. Proper squeegeeing will decrease surface cure time and avoid tracking of **KOLD-FLO** crack filler. A second application may be necessary for cracks deeper than 2 inches.

### Coverage per gallon

1/4" w x 1/4" d = 300 linear feet  
1/2" w x 1/2" d = 75 linear feet  
1" w x 1" d = 25 linear feet

**CRACK-N-TACK.**  
PORTABLE PUMP  
.....

KOLD-FLO® is a registered trademark of UNIQUE Paving Materials Corp.



Corporate Office | 800.441.4880 | 3993 E. 93rd Street, Cleveland, OH 44105 | [uniquepavingmaterials.com](http://uniquepavingmaterials.com)

# KOLD-FLO®

Pourable Crack Filler

## QUESTIONS & ANSWERS

### What type of crack filler is KOLD-FLO® crack filler?

**KOLD-FLO** crack filler is a specially formulated, polymer modified asphalt based emulsion designed to be used to crack fill in asphalt and concrete pavements.

**Does sand need to be applied on KOLD-FLO crack filler after application?** NO! **KOLD-FLO** crack filler will surface cure between 15 and 30 minutes after application allowing for quick traffic access. Extreme cases of humidity may prolong curing up to 45 minutes. **KOLD-FLO** crack filler takes at least 8 hours to completely cure. Without proper curing, **KOLD-FLO** crack filler may become susceptible to rain washout.

**Is KOLD-FLO crack filler affected by freezing temperatures?** YES! Freezing temperatures will destroy **KOLD-FLO** crack filler during storage or within 24 hours of application.



**Do I need to mix or heat KOLD-FLO crack filler?** NO! **KOLD-FLO** crack filler is ready-to-use right from the container. If settling occurs from prolonged storage, nominal agitation may be necessary.

**Can you sealcoat over KOLD-FLO crack filler?** YES! We recommend allowing **KOLD-FLO** crack filler to cure for 24 hours before sealcoating. Smaller cracks may be sealed over earlier once **KOLD-FLO** crack filler has cured.

**What is the shelf life of KOLD-FLO crack filler?** 6 months minimum when stored properly.

**What sizes are KOLD-FLO crack filler available?** **KOLD-FLO** crack filler is conveniently packaged in 1-gallon bottles, 5-gallon pails and 55-gallon drums.

### *Distributed by:*

KOLD-FLO® is a registered trademark of UNIQUE Paving Materials Corp.



Corporate Office | 800.441.4880 | 3993 E. 93rd Street, Cleveland, OH 44105 | [uniquepavingmaterials.com](http://uniquepavingmaterials.com)