

UNIQUE® CONCRETE SEALER



Protect concrete surfaces from water damage caused by freeze/thaw cycles, stains from dirt, deicing salts, oil, and other contaminants.

Product Description

UNIQUE® Concrete Sealer is a penetrating non-yellowing acrylic polymer ASTM C-309 VOC compliant concrete sealer designed to form a protective barrier for new and old concrete against water and deicing salts. It can also be used as a dustproofing treatment.

Benefits / Features

- Ready to use
- Simple application; spray or roller
- Reduces surface porosity
- Excellent adhesion to pavement surfaces
- UV resistant
- Breathable
- Slip-resistant, even when wet
- Environmentally friendly, water-based formulation
- Non-hazardous

Recommended Uses

Use to seal new and sound aged concrete pavements to protect concrete surfaces from water damage caused by freeze/thaw cycles, stains from dirt, deicing salts, oil, and other contaminants.

Placement

The surface should be dry. Sealer can be applied directly from the container with a hand-held pump pressure sprayer or with automated spray equipment. It can also be roller applied. Multiple coats may be applied for heavy traffic areas. Allow 2-4 hours curing time between coats.

Coverage Rate

One gallon of UNIQUE® Concrete Sealer will cover approximately 150 square feet (50 square yards). Coverage rate will vary due to age, surface condition, and porosity.

Shelf Life

Twelve months in an unopened container.



3993 East 93rd Street

Cleveland, OH 44105

800.441.4880

UniquePavingMaterials.com

UNIQUE® CONCRETE SEALER is manufactured by UNIQUE Paving Materials Corp.

UNIQUE® is a registered trademark of UNIQUE Paving Materials Corp.

UNIQUE®
CONCRETE
SOLUTIONS